



Ball valve coloro type 353 PVC-U
With solvent cement sockets ASTM/BS

Model:

- Compact
- Monobloc structure
- Lever orange
- Ball seal PTFE
- Only bulk pack GP are delivered
- Actuator unit not connectable

Size (inch)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
½	15	16	161 353 342	12	0.069	161 353 352	12	0.074
¾	20	16	161 353 343	12	0.104	161 353 353	12	0.097
1	25	16	161 353 344	12	0.148	161 353 354	12	0.147
1 ¼	32	16	161 353 345	6	0.222	161 353 355	6	0.222
1 ½	40	16	161 353 346	6	0.460	161 353 356	6	0.310
2	50	16	161 353 347	6	0.647	161 353 357	6	0.647

Size (inch)	D (mm)	H (mm)	L (mm)	L1 (mm)	z (mm)
½	49	51	77	78	33
¾	54	58	89	92	38
1	64	63	105	92	48
1 ¼	78	77	119	116	56
1 ½	90	83	136	116	66
2	112	102	160	140	83

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>