

Dryout Thermostats

Features

- Two-wire installation
- Four fixed setpoint models to choose from 60°F to 75°F
- Temporary use for dryout applications
- Can be used as a low ambient cutoff switch



Specifications

- Input: 18-30 VAC
- Output: 2 amp maximum
- Temperature Control Range: 60°F to 75°F (±9°F)

| Item ID | Dryout Thermostats | | | |
|-------------------|--------------------|----------|----------|----------|
| | SC060 | SC065 | SC070 | SC075 |
| Temperature Range | 60°F ±9° | 65°F ±9° | 70°F ±9° | 75°F ±9° |
| 2-Wire | • | • | • | • |
| Heat | • | • | • | |
| Cool | | | | • |

Air Pressure Sensing Switch Kits



Manufactured by
CLEVELAND CONTROLS

Features

- Mounts with the diaphragm in vertical plane
- Easy installation
- Designed for residential furnace and light commercial aftermarket applications; duct heater, oven, and other HVAC or energy management applications



| Item ID | Description | Range | Operating Temp. Range | Contact Arrangement | Connection | Approval |
|----------------|-----------------------------|---------------------|-----------------------|---------------------|------------------------------|----------|
| Packard | | | | | | |
| PS000 | Field Adjustable Switch Kit | 0.10"wc To 10.0"wc. | -40F To 190F | SPDT | 1/4" Quick-Connect Terminals | UL, CUL |



| Item ID | Description | Range | Operating Temp. Range | Contact Arrangement | Connection | Approval |
|----------------|-----------------------------|--------------------|-----------------------|---------------------|------------------------------------|----------|
| Packard | | | | | | |
| PS495 | Field Adjustable Switch Kit | 0.20"wc To 1.0"wc. | -40F To 190F | SPDT | 3 Male 90° Quick-Connect terminals | UL |



| Item ID | Description | Range | Operating Temp. Range | Contact Arrangement | Connection | Approval |
|----------------|-----------------------------|-------------------|-----------------------|---------------------|------------------------------------|----------|
| Packard | | | | | | |
| PS498 | Field Adjustable Switch Kit | 1.0"wc To 4.0"wc. | -40F To 190F | SPDT | 3 Male 90° Quick-Connect terminals | UL |



| Item ID | Description | Range | Operating Temp. Range | Contact Arrangement | Connection | Approval |
|----------------|-----------------------------|---------------------|-----------------------|---------------------|--------------------------------------|----------|
| Packard | | | | | | |
| PS222 | Field Adjustable Switch Kit | 0.05"wc To 12.0"wc. | -40F To 180F | SPDT | Screw Top Terminals With Cup Washers | UL |

